

**Description**

Fastener Length: 3/16", Thread: 4-40, Thread Length: 3/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS119004P3                               |
| Minimum Qty (MOQ):      | 35 EA                                     |
| NSN:                    | 5305-00-143-3300                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

# P/N NAS1190-04P3 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.107 Inches Minimum And 0.188 Inches Maximum  |
| <b>Fastener Length:</b>                               | 0.157 Inches Minimum And 0.188 Inches Maximum  |
| <b>Head Style:</b>                                    | Pan  |
| <b>Head Diameter:</b>                                 | 0.205 Inches Minimum And 0.219 Inches Maximum  |
| <b>Head Height:</b>                                   | 0.070 Inches Minimum And 0.080 Inches Maximum  |
| <b>Internal Drive Style:</b>                          | Cross Recess Type 1  |
| <b>Nominal Thread Diameter:</b>                       | 0.112 Inches   |
| <b>Thread Quantity Per Inch:</b>                      | 40   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch  |
| <b>Hardness Rating:</b>                               | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  |
| <b>Hardness Rating:</b>                               | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum Overall  |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads   |
| <b>Material:</b>                                      | Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall   |
| <b>Material:</b>                                      | Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740 Overall   |
| <b>Material Document And Classification:</b>          | Mils-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall |
| <b>Material Document And Classification:</b>          | Mils-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material Response Overall                 |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall   |
| <b>Surface Treatment:</b>                             | Cadmium And Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>                      | Unjc   |
| <b>Specification/standard Data:</b>                   | 80205-nas1190 Professional/Industrial Association Standard   |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1190-04P3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.