

P/N NAS1190-04P5HB

Description

Fastener Length: 5/16", Thread: 4-40, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS119004P5HB

Minimum Qty (MOQ): 15 EA

NSN: 5305-01-513-8374

Schedule B: 7318.15.2010

ECCN: 9A991

National Motor Freight: 096640, Screws, Iron Or Steel



^{*} See page 2 for technical characteristics

P/N NAS1190-04P5HB Specifications

| Thread Class: | 3a |
|--|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.3125 Inches Nominal |
| Fastener Length: | 0.3125 Inches Nominal |
| Head Style: | Pan No. 2 |
| Head Diameter: | 0.205 Inches Minimum And 0.219 Inches Maximum |
| Head Height: | 0.070 Inches Minimum And 0.080 Inches Maximum |
| Locking Feature: | Patch |
| Internal Drive Style: | Cross Recess Type Iii |
| End Item Identification: | 15 Ton Vapor |
| Nominal Thread Diameter: | 0.112 Inches |
| Thread Quantity Per Inch: | 40 |
| Screw Material: | Steel Comp 4140 Or Steel Comp 4340 Or Steel Comp 8740 |
| Screw Material Document And Classification: | Mil-s-5626 Mil Spec 1st Material Response Or Ams 6415 Assn Std 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material Response |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Qq-p-416, Type 2, Class 2 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unjc |

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS1190-04P5HB and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.