

## P/N NAS1190-04P5HB

## **Description**

Fastener Length: 5/16", Thread: 4-40, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS119004P5HB

Minimum Qty (MOQ): 15 EA

NSN: 5305-01-513-8374

Schedule B: 7318.15.2010

ECCN: 9A991

National Motor Freight: 096640, Screws, Iron Or Steel



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1190-04P5HB Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.3125 Inches Nominal
Fastener Length:	0.3125 Inches Nominal
Head Style:	Pan No. 2
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Locking Feature:	Patch
Internal Drive Style:	Cross Recess Type Iii
End Item Identification:	15 Ton Vapor
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Screw Material:	Steel Comp 4140 Or Steel Comp 4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Or Ams 6415 Assn Std 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416, Type 2, Class 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS1190-04P5HB">https://military-fasteners.com/screws/machine+screws/NAS1190-04P5HB</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.