

**Description**

Fastener Length: 5/16", Thread: 4-40, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS119004P5HB
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-513-8374
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE  
AVAILABLE

## P/N NAS1190-04P5HB Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.3125 Inches Nominal
<b>Fastener Length:</b>	0.3125 Inches Nominal
<b>Head Style:</b>	Pan No. 2
<b>Head Diameter:</b>	0.205 Inches Minimum And 0.219 Inches Maximum
<b>Head Height:</b>	0.070 Inches Minimum And 0.080 Inches Maximum
<b>Locking Feature:</b>	Patch
<b>Internal Drive Style:</b>	Cross Recess Type Iii
<b>End Item Identification:</b>	15 Ton Vapor
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Thread Quantity Per Inch:</b>	40
<b>Screw Material:</b>	Steel Comp 4140 Or Steel Comp 4340 Or Steel Comp 8740
<b>Screw Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Or Ams 6415 Assn Std 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material Response
<b>Screw Surface Treatment:</b>	Cadmium
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416, Type 2, Class 2 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1190-04P5HB> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.