

**Description**

Fastener Length: 5/16", Thread: 4-40, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                               |
|-------------------------|-------------------------------|
| SKU / Model:            | NAS119004P5HB                 |
| Minimum Qty (MOQ):      | 15 EA                         |
| NSN:                    | 5305-01-513-8374              |
| Schedule B:             | 7318.15.2010                  |
| ECCN:                   | 9A991                         |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE  
AVAILABLE

## P/N NAS1190-04P5HB Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>                                    | Right-hand  |
| <b>Thread Length:</b>                                       | 0.3125 Inches Nominal   |
| <b>Fastener Length:</b>                                     | 0.3125 Inches Nominal   |
| <b>Head Style:</b>  | Pan No. 2   |
| <b>Head Diameter:</b>                                       | 0.205 Inches Minimum And 0.219 Inches Maximum   |
| <b>Head Height:</b>   | 0.070 Inches Minimum And 0.080 Inches Maximum   |
| <b>Locking Feature:</b>                                     | Patch   |
| <b>Internal Drive Style:</b>                                | Cross Recess Type Iii   |
| <b>End Item Identification:</b>                             | 15 Ton Vapor  |
| <b>Nominal Thread Diameter:</b>                             | 0.112 Inches  |
| <b>Thread Quantity Per Inch:</b>                            | 40  |
| <b>Screw Material:</b>                                      | Steel Comp 4140 Or Steel Comp 4340 Or Steel Comp 8740   |
| <b>Screw Material Document And Classification:</b>          | Mil-s-5626 Mil Spec 1st Material Response Or Ams 6415 Assn Std 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material Response |
| <b>Screw Surface Treatment:</b>                             | Cadmium   |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-416, Type 2, Class 2 Fed Spec Single Treatment Response  |
| <b>Thread Series Designator:</b>                            | Unjc  |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1190-04P5HB> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.