



Military-Fasteners.com

P/N NAS1190-04P6N

Description

Fastener Length: 3/8", Thread: 4-40, Thread Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS119004P6N
Minimum Qty (MOQ):	10
NSN:	5305-01-051-0632
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N NAS1190-04P6N Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.294 Inches Minimum And 0.375 Inches Maximum
Fastener Length:	0.344 Inches Minimum And 0.375 Inches Maximum
Head Style:	Pan
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Locking Feature:	Pellet Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-0-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1190 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1190-04P6N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.