

# P/N NAS1190-06P10B

### **Description**

Fastener Length: 5/8", Thread: 6-32, Thread Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS119006P10B
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-438-8263
Schedule B:	7318.15.6080

9A991



ECCN:

<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1190-06P10B Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.625 Inches Nominal
Fastener Length:	0.594 Inches Minimum And 0.625 Inches Maximum
Head Style:	Pan
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Screw Material:	Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740
Thread Series Designator:	Unjc

# **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS1190-06P10B">https://military-fasteners.com/screws/machine+screws/NAS1190-06P10B</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/MAS1190-06P10B">https://military-fasteners.com/screws/machine+screws/NAS1190-06P10B</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/MAS1190-06P10B">https://military-fasteners.com/screws/MAS1190-06P10B</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/MAS1190-06P10B">https://military-fasteners.com/screws/MAS1190-06P10B</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/mashed-pasteners.com/screws/mashed-