

P/N NAS1190-06P6L

Description

Fastener Length: 3/8", Thread: 6-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS119006P6L

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-822-1666

Schedule B: 7318.15.2010

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1190-06P6L Specifications

| Thread Class: | 3a |
|---|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.282 Inches Minimum And 0.375 Inches Maximum |
| Fastener Length: | 0.344 Inches Minimum And 0.375 Inches Maximum |
| Head Diameter: | 0.256 Inches Minimum And 0.270 Inches Maximum |
| Head Height: | 0.087 Inches Minimum And 0.097 Inches Maximum |
| Nominal Thread Diameter: | 0.138 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Part Name Assigned By Controlling Agency: | Screw Pan Head Self Locking |
| Thread Series Designator: | Unjc |
| Specification/standard Data: | 80205-nas1190 Professional/industrial Association Standard |

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS1190-06P6L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS1190-06P6L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS1190-06P6L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS1190-06P6L and selecting the quantity you want of the property of the property