

P/N NAS1190-08P16B

Military-Fasteners.com

Description

Fastener Length: 0-63/64", Thread: 8-32, Thread Length: 0-63/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS119008P16B
Minimum Qty (MOQ):	40 EA
NSN:	5305-01-064-2339
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1190-08P16B Specifications

Thread Direction:Right-handThread Direction:Right-handThread Length:0.907 Inches Minimum And 1.000 Inches MaximumFastener Length:0.969 Inches Minimum And 1.000 Inches MaximumHead Style:PanHead Bight:0.306 Inches Minimum And 0.322 Inches MaximumHead Height:0.306 Inches Minimum And 0.322 Inches MaximumLocking Feature:Patch ThreadsInternal Drive Style:Cross Recess Type 1Nomian Thread Diameter:0.164 Inches1.66 Inches Minimum Overall And 40.00 Rockwell C Maximum OverallMinimum Tensile Strength:160000 Pounds Per Square InchMinimum Tensile Strength:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Noticniches ThreadsMaterial:Stel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial:Stel Comp 4140 Fastener Or Mil-s-6844 Mil Spec 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Mil-s-6044 Mil Spec 3rd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Odrium Fastener And Chromate FastenerSurface Treatment:Odrium Fastener And Chromate FastenerSurface Treatment:UnjcUnicassification:Unica		
Thread Length:0.907 Inches Minimum And 1.000 Inches MaximumFastener Length:0.969 Inches Minimum And 1.000 Inches MaximumHead Style:PanHead Diameter:0.306 Inches Minimum And 0.322 Inches MaximumLocking Feature:Patch ThreadsInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.164 InchesVominal Thread Diameter: <t< th=""><td>Thread Class:</td><td>За</td></t<>	Thread Class:	За
Fastener Length:0.969 Inches Minimum And 1.000 Inches MaximumHead Style:PanHead Diameter:0.306 Inches Minimum And 0.322 Inches MaximumHead Height:0.105 Inches Minimum And 0.115 Inches MaximumLocking Feature:Patch ThreadsInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.164 Inches0.164 Inches1.64 InchesThread Quantity Per Inch:3236. Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallBurface Finish:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:2.0 Microinches ThreadsMaterial:Pastic Polyamide Locking FeatureMaterial:Stel Comp 4140 Fastener Or Stel Comp 4340 Fastener Or Stel Comp 8740 FastenerMaterial Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2rdSurface Treatment:Candim Fastener And Chromate FastenerSurface Treatment:Unip: Cl2 Fed Spec Single Treatment Response FastenerSurface Treatment:Unip:	Thread Direction:	Right-hand
Head Style:PanHead Diameter:0.306 Inches Minimum And 0.322 Inches MaximumHead Height:0.105 Inches Minimum And 0.115 Inches MaximumLocking Feature:Patch ThreadsInternal Drive Style:Cross Recess Type 1Nomial Thread Diameter:0.164 Inches0.164 Inches32Minimum Tensile Strength:16000 Pounds Per Square Inch30.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Pastic Polyamide Locking FeatureMaterial:Neise Sourg 1.526 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Classification:Surface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment: </th <td>Thread Length:</td> <td>0.907 Inches Minimum And 1.000 Inches Maximum</td>	Thread Length:	0.907 Inches Minimum And 1.000 Inches Maximum
Head Diameter:0.306 Inches Minimu And 0.322 Inches MaximumHead Height:0.105 Inches Minimu And 0.115 Inches MaximumLocking Feature:Patch ThreadsInternal Drive Style:Cross Recess Type 1Nomial Thread Diameter:0.164 Inches0.164 Inches32Minimum Tensile Strength:160000 Pounds Per Square InchMarchas Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Pastic Polyamide Locking FeatureMaterial:Comp 1410 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial:Cadmium Fastener Or Mil-s-6844 Mil Spec 2nd Material Response Fastener Or Mil-s-6844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2ndSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerThread Series Designator:Unjc	Fastener Length:	0.969 Inches Minimum And 1.000 Inches Maximum
Head Height:0.105 Inches Minimum And 0.115 Inches MaximumLocking Feature:Patch ThreadsInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.164 Inches0.164 Inches32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Material Response Fastener Or Mil-s-6844 Mil Spec 2nd Material Response Fastener Or Amis-6149 Mil Spec 3rd Material Response Fastener Or Amis-6149 Mil Spec 3rd Material Response FastenerSurface Treatment:camium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qr-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjc	Head Style:	Pan
Locking Feature:Patch ThreadsInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.164 InchesDumber Style:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Respons	Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Internal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.164 InchesThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches Bearing Surface Of HeadMaterial:Plastic Polyamide Locking FeatureMaterial:Stel Comp 4140 Fastener Or Stel Comp 4340 Fastener Or Stel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Mil-s-6	Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Nominal Thread Diameter:0.164 InchesDominal Thread Quantity Per Inch:32Minimu Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches Bearing Surface Of HeadMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3nd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:op-p416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjc	Locking Feature:	Patch Threads
Thread Quantity Per Inch:32Thread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches Bearing Surface Of HeadMaterial:Plastic Polyamide Locking FeatureMaterial:Veel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Q-q-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjc	Internal Drive Style:	Cross Recess Type 1
Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Pastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mils-s5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Amis-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qu-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjc	Nominal Thread Diameter:	0.164 Inches
Hardness Rating:36.0 Rockwell C Minimun Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Q-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjc	Thread Quantity Per Inch:	32
Surface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerMires Designator:Unjc	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerUnjcUnjc	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:Plastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Q-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerUnjc	Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjc	Surface Finish:	32.0 Microinches Threads
Material Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:op-9416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unic	Material:	Plastic Polyamide Locking Feature
Classification:Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment Document And Classification:Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjc	Material:	Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 Fastener
Surface Treatment Document And Classification:Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjc	Material Document And Classification:	
Classification: Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Fastener Thread Series Designator: Unjc	Surface Treatment:	Cadmium Fastener And Chromate Fastener
	Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Fastener
Specification/standard Data: 80205-nas1190 Professional/industrial Association Standard	Thread Series Designator:	Unjc
	Specification/standard Data:	80205-nas1190 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/NAS1190-08P16B</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.