

## P/N NAS1190-08P22B

## **Description**

Fastener Length: 1-3/8", Thread: 8-32, Thread Length: 1-3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: NAS119008P22B

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-063-3776

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1190-08P22B Specifications

| Thread Class:                                  | 2a  |
|--|---|
| Thread Direction:                              | Right-hand  |
| Thread Length:                                 | 1.251 Inches Minimum And 1.375 Inches Maximum   |
| Fastener Length:                               | 1.313 Inches Minimum And 1.375 Inches Maximum   |
| Head Style:                                    | Pan   |
| Head Diameter:                                 | 0.306 Inches Minimum And 0.322 Inches Maximum   |
| Head Height:                                   | 0.105 Inches Minimum And 0.115 Inches Maximum   |
| Locking Feature:                               | Patch Threads   |
| Internal Drive Style:                          | Cross Recess Type 1   |
| Nominal Thread Diameter:                       | 0.164 Inches  |
| Thread Quantity Per Inch:                      | 32  |
| Minimum Tensile Strength:                      | 160000 Pounds Per Square Inch   |
| Hardness Rating:                               | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall   |
| Surface Finish:                                | 32.0 Microinches Bearing Surface Of Head  |
| Surface Finish:                                | 32.0 Microinches Threads  |
| Material:                                      | Plastic Polyamide Locking Feature   |
| Material:                                      | Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 Fastener  |
| Material Document And Classification:          | Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener |
| Surface Treatment:                             | Cadmium Fastener And Chromate Fastener  |
| Surface Treatment Document And Classification: | Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Fastener  |
| Thread Series Designator:                      | Unjc  |
| Specification/standard Data:                   | 80205-nas1190 Professional/industrial Association Standard  |

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS1190-08P22B">https://military-fasteners.com/screws/machine+screws/NAS1190-08P22B</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/MAS1190-08P22B">https://military-fasteners.com/screws/machine+screws/NAS1190-08P22B</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/MAS1190-08P22B">https://military-fasteners.com/screws/MAS1190-08P22B</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/MAS1190-08P22B">https://military-fasteners.com/screws/MAS1190-08P22B</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/mashed-pasteners.com/screws/mashed-