

P/N NAS1190-08P22B

Military-Fasteners.com

#### Description

Fastener Length: 1-3/8", Thread: 8-32, Thread Length: 1-3/8"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	NAS119008P22B
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-063-3776
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N NAS1190-08P22B Specifications

Thread Class:2aThread Direction:Right-handThread Length:1.251 Inches Minimum And 1.375 Inches MaximumFastener Length:1.313 Inches Minimum And 1.375 Inches MaximumHead Style:PanHead Diameter:0.306 Inches Minimum And 0.322 Inches MaximumLeckling Feature:Patch ThreadsLockling Feature:Patch ThreadsInternal Drive Style:Cross Recess Type 1Noninal Thread Diameter:0.106 Inches Minimum And 0.115 Inches MaximumNoninal Thread Diameter:0.106 Inches Style:Sufface Finish:0.106 Inches Style:Sufface Finish:0.600 Pounds Per Square InchMaterial:16000 Pounds Per Square InchSufface Finish:32.0 Microinches Bearing Sufface Of HeadSufface Finish:32.0 Microinches ThreadsMaterial:19.812 Polyamide Lockling FeatureMaterial:9.814 Polyamide Lockling FeatureMaterial:Sufface Stelesion Sufface Of Mil-Seatener Or Mil-Seatener Or Mil-Seatener Or Mil-SeatenerMaterial:Sufface Stelesion Mil Spec 2 nd Material Response Fastener Or Mil-SeatenerMaterial:Sufface Treatment:Sufface Treatment Document And Classification:Sufface Stelesion Mil-Seatener Or Mil-SeatenerClassifica		
Thread Length:2.51 Inches Minimu And 1.375 Inches MaximumFastener Length:1.313 Inches Minimu And 1.375 Inches MaximumHead Style:PanHead Diameter:0.306 Inches Minimu And 0.322 Inches MaximumHead Diameter:0.105 Inches Minimu And 0.322 Inches MaximumLocking Feature:Patch ThreadsInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.164 Inches0.164 InchesSecess Type 1Nominal Thread Diameter:0.164 Inches0.164 Nones Per Square Inch32Minimum Tensile Strength:160000 Pounds Per Square InchMarfaer E Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches Bearing Surface Of HeadMaterial:Pastic Polyamide Locking FeatureMaterial:Instri Schops Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2ndMaterial:Camp Inter And Chromate FastenerSurface Treatment Document And Classification:Camp Inter And Chromate FastenerSurface Treatment Document And Classification:Camp Inter And Chromate FastenerSurface Treatment Document And Classification:Gap-216 Ty2 Li2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjc	Thread Class:	2a
Pastener Length:1.313 Inches Minimum And 1.375 Inches MaximumHead Style:PanHead Diameter:0.306 Inches Minimum And 0.322 Inches MaximumHead Height:0.105 Inches Minimum And 0.115 Inches MaximumLocking Feature:Patch ThreadsInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.164 Inches0.164 Inches32Minimum Tensile Strength:160000 Pounds Per Square InchBarder Finish:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Baring Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Pasten Or Style: Comp 4140 Fastener Or Stele Comp 4340 Fastener Or Stele Comp 8740 FastenerMaterial:Stele Comp 4140 Fastener Or Stele Comp 4340 Fastener Or Stele Comp 8740 Fastener Or Ams6414 Assn Std 2ndMaterial Response Fastener Or Mil-s-6044 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2ndSurface Treatment Document And Classification:Mil-s5262 Mil Spec 1st Material Response Fastener Or Mil-s-6044 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2ndSurface Treatment Document And Classification:Caminum Fastener And Chromate FastenerSurface Treatment Document And Classification:Qin-416T Spec Single Treatment Response FastenerSurface Treatment Document And Classification:Qin-416T Spec Single Treatment Response FastenerSurface Treatment Document And Classification:Mil-s262 Mil Spec 1st Material Response FastenerSurface Treatment Document And Classification:Unipic Clastener Corticate	Thread Direction:	Right-hand
Head Style:PanHead Diameter:0.306 Inches Minimum And 0.322 Inches MaximumHead Height:0.105 Inches Minimum And 0.115 Inches MaximumLocking Feature:Patch ThreadsInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.164 Inches0.164 Inches0.000 Pounds Per Square Inch32Goodo Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Pastic Polyamide Locking FeatureMaterial:Pastic Polyamide Locking FeatureMaterial:Stel Comp 4140 Fastener Or Stel Comp 4340 Fastener Or Stel Comp 8740 FastenerMaterial:Mils-S520 Mil Spec. Ist Material Response Fastener Or Mil-s-8844 Mil Spec. 2nd Material Response Fastener Or Mil-s-8844 Mil Spec. 2nd Material Response Fastener Or Ams6414 Assn Std 2ndSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment:Unjc	Thread Length:	1.251 Inches Minimum And 1.375 Inches Maximum
Head Diameter:0.306 Inches Minimu And 0.322 Inches MaximumHead Height:0.105 Inches Minimu And 0.115 Inches MaximumLocking Feature:Patch ThreadsInternal Drive Style:Cross Recess Type 1Nomial Thread Diameter:0.164 Inches0.164 Inches32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:0.60 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Patci Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial:Steel Comp 4140 Fastener Or Mil-s-68444 Mil Spec 2nd Material Response Fastener Or Mil-s-6844 Mil Spec 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3nd Material Response	Fastener Length:	1.313 Inches Minimum And 1.375 Inches Maximum
Head Height:0.105 Inches Minimum And 0.115 Inches MaximumLocking Feature:Patch ThreadsInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.164 Inches0.164 Inches32Thread Quantity Per Inch:3236.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Patsic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Of Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fast	Head Style:	Pan
Locking Feature:Patch ThreadsInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.164 InchesThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Pastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial:Cadmium Fastener And Chromate Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Q-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjc	Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Internal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.164 InchesThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Stel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment:Oq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerSurface Sries Designator:Unic	Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Nominal Thread Diameter:0.164 InchesInread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qr-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjc	Locking Feature:	Patch Threads
Thread Quantity Per Inch:32Minimur Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches Bearing Surface Of HeadMaterial:Plastic Polyamide Locking FeatureMaterial:Veel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Q-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerSurface Treatment Document And Classification:Unjc	Internal Drive Style:	Cross Recess Type 1
Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Q-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerMurface Treatment Document And Classification:Unjc	Nominal Thread Diameter:	0.164 Inches
Hardness Rating:36.0 Rockwell C Minimun Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Or-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjc	Thread Quantity Per Inch:	32
Surface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Q-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjc	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerUnjc	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:Plastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerUnjc	Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjc	Surface Finish:	32.0 Microinches Threads
Material Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerDiscurtation:Unic	Material:	Plastic Polyamide Locking Feature
Classification:Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unic	Material:	Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 Fastener
Surface Treatment Document And Classification:Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjc		
Classification: Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Fastener   Thread Series Designator: Unjc	Surface Treatment:	Cadmium Fastener And Chromate Fastener
		Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Fastener
Specification/standard Data: 80205-nas1190 Professional/industrial Association Standard	Thread Series Designator:	Unjc
	Specification/standard Data:	80205-nas1190 Professional/industrial Association Standard

## How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/NAS1190-08P22B</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.