

P/N NAS1190-08P30B

Military-Fasteners.com

Description

Fastener Length: 1-7/8", Thread: 8-32, Thread Length: 1-7/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS119008P30B
Minimum Qty (MOQ):	20 EA
NSN:	5305-01-064-3592
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



P/N NAS1190-08P30B Specifications

Thread Class:3aThread Jirection:Right-handThread Length:1.751 Inches Minimum And 1.875 Inches MaximumFastener Length:1.813 Inches Minimum And 1.875 Inches MaximumHead Style:PanHead Dlameter:0.306 Inches Minimum And 0.322 Inches MaximumHead Height:0.105 Inches Minimum And 0.115 Inches MaximumLocking Feature:Patch ThreadsInternal Drive Style:Orss Recess Type 1Nomian Thread Diameter:0.160 Inches Minimum And 0.022 Inches MaximumNomian Thread Diameter:0.164 InchesMinimum Tensile Strength:0.600 Pounds Per Square InchSurface Finish:0.600 Pounds Per Square InchSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:0.20 Microinches ThreadsMaterial:Patci Paty-mied Locking Feature:Material:Natic Palymied Locking Feature:Material:Natic Palymied Locking Feature:Material:Mil-5520 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Mil-S-8844 Mil Spec 2nd Material Response Fastener Or Mil-S-6844 Mil Spec 2nd Material Response Fastener Or Mil-S-6844 Mil Spec 2nd Material Response Fastener Or Mil-S-6844 Mil Spec 2nd Material Response Fastener Or Mil-S-6849 Mil Spec 2nd Material Response Fastener Or Mil-S-6844 Mil Spec 2nd Material Response Fastener Or Mil-S-6049 Mil Spec 2nd Material Response Fastener O		
Thread Length:1.751 Inches Minimu And 1.875 Inches MaximumFastener Length:1.813 Inches Minimu And 1.875 Inches MaximumHead Style:PanHead Diameter:0.306 Inches Minimu And 0.322 Inches MaximumHead Height:0.105 Inches Minimu And 0.115 Inches MaximumLocking Feature:Patch ThreadsInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.164 Inches0.164 InchesScecess Type 1Nominal Thread Diameter:0.164 Inches0.164 Inches32Minimum Tensile Strength:16000 Pounds Per Square InchHardess Rating:0.60 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:Scu Microinches ThreadsMaterial:Pastic Polyamide Locking FeatureMaterial:Steel Comp 1410 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial:Camp Interial Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2ndSurface Treatment:Cambum Fastener And Chromate FastenerSurface Treatment:Cambum Fastener And Chromate FastenerSurface Treatment:Cambum Fastener And Chromate FastenerSurface Treatment:Gunu Fastener And Chromate FastenerSurface Treatment:Unjc	Thread Class:	За
Pastener Length:1.813 Inches Minimum And 1.875 Inches MaximumHead Style:PanHead Diameter:0.306 Inches Minimum And 0.322 Inches MaximumHead Height:0.105 Inches Minimum And 0.115 Inches MaximumLocking Feature:Patch ThreadsInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.164 Inches0.164 Inches32Minimum Tensile Strength:16000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Paster Or Style: Comp 4340 Fastener Or Style Comp 4340 Fastener Or Style Comp 4340 Fastener Or Style Comp 4340 FastenerMaterial:Stel Comp 4140 Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Styl 2ndSurface Treatment:Camima Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Mil-s-6049 Mil Sp	Thread Direction:	Right-hand
Head Style:PanHead Diameter:0.306 Inches Minimum And 0.322 Inches MaximumHead Height:0.105 Inches Minimum And 0.115 Inches MaximumLocking Feature:Patch ThreadsInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.164 Inches0.164 Inches32Minimum Tensile Strength:16000 Pounds Per Square InchMarinaum Tensile Strength:36.00 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Pastic Polyamide Locking FeatureMaterial:Nord 14.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Pastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2ndMaterial Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2ndSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment:Cadmium Fastener And Chromate Fastener	Thread Length:	1.751 Inches Minimum And 1.875 Inches Maximum
Head Diameter:0.306 Inches Minimu And 0.322 Inches MaximumHead Height:0.105 Inches Minimu And 0.115 Inches MaximumLocking Feature:Patch ThreadsInternal Drive Style:Cross Recess Type 1Nomial Thread Diameter:0.164 Inches0.164 Inches32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Patsic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial:Steel Comp 4140 Fastener Or Mil-s-6844 Mil Spec 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3nd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment:	Fastener Length:	1.813 Inches Minimum And 1.875 Inches Maximum
Head Height:0.105 Inches Minimum And 0.115 Inches MaximumLocking Feature:Patch ThreadsInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.164 Inches0.164 Inches32Thread Quantity Per Inch:32360000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Patsic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Cadmium Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener Or Steel Comp 8740 FastenerSurface Treatment:Cadmium Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerMaterial Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerMaterial Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerMaterial Response Fastener Or Mi	Head Style:	Pan
Locking Feature:Patch ThreadsInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.164 InchesDominal Thread Diameter:0.164 InchesThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp 1440 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Cadmium Fastener And Chromate FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment:Unjc	Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Internal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.164 InchesThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:22.0 Microinches Bearing Surface Of HeadSurface Finish:23.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Stel Comp 4140 Fastener Or Stel Comp 4340 Fastener Or Stel Comp 8740 FastenerMaterial Document And Classification:Wils-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:UnjcUnicUnic	Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Nominal Thread Diameter:0.164 InchesThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Mil-s-8049 Mil Spec 3rd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Or-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerMaterial Series Designator:Unjc	Locking Feature:	Patch Threads
Thread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches Bearing Surface Of HeadMaterial:Plastic Polyamide Locking FeatureMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Q-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerSurface Treatment Document And Classification:Unjc	Internal Drive Style:	Cross Recess Type 1
Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Q-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerMuf Series Designator:Unjc	Nominal Thread Diameter:	0.164 Inches
Hardness Rating:36.0 Rockwell C Minimu Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Q-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjc	Thread Quantity Per Inch:	32
Surface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Q-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerSurface Treatment Document And Classification:Unjc	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerUnjcUnjc	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:Plastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerUnjc	Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material:Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjc	Surface Finish:	32.0 Microinches Threads
Material Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-8844 Mil Spec 2nd Material Response Fastener Or Ams6414 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerDuble Classification:Unic	Material:	Plastic Polyamide Locking Feature
Classification:Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unic	Material:	Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener Or Steel Comp 8740 Fastener
Surface Treatment Document And Classification:Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjc		
Classification: Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Fastener Thread Series Designator: Unjc	Surface Treatment:	Cadmium Fastener And Chromate Fastener
		Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Fastener
Specification/standard Data: 80205-nas1190 Professional/industrial Association Standard	Thread Series Designator:	Unjc
	Specification/standard Data:	80205-nas1190 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/NAS1190-08P30B</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.