

Description

Fastener Length: 5/16", Thread: 8-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS119008P5 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-386-0928 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093490, Bolt / Nut / Screw / Clips / Fastener / Etc |

NO IMAGE
AVAILABLE

P/N NAS1190-08P5 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.251 Inches Nominal |
| Fastener Length: | 0.313 Inches Nominal |
| Head Style: | Pan No. 2 |
| Head Diameter: | 0.306 Inches Minimum And 0.322 Inches Maximum |
| Head Height: | 0.105 Inches Minimum And 0.115 Inches Maximum |
| Locking Feature: | Patch Or Pellet Or Strip |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Screw Material: | Steel Comp 4140 Or Steel Comp 4340 Or Steel Comp 8740 |
| Locking Feature Material: | Plastic Polyamide |
| Screw Material Document And Classification: | Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-8844 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material Response |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response |
| Bearing Surface Of Head Surface Finish: | 32.0 Microinches |
| Shank Surface Finish: | 32.0 Microinches |
| Thread Surface Finish: | 32.0 Microinches |
| Thread Series Designator: | Unjc |
| Specification/standard Data: | 80205-nas1190 Professional/industrial Association Standard |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1190-08P5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.