

Description

Fastener Length: 3/8", Thread: 10-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS11903P6
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-229-4877
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1190-3P6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.282 Inches Minimum And 0.375 Inches Maximum
Fastener Length:	0.344 Inches Minimum And 0.375 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1190 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1190-3P6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.