

P/N NAS1190-3P7

Description

Fastener Length: 7/16", Thread: 10-32, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS11903P7

Minimum Qty (MOQ): 15 EA

NSN: 5305-01-009-6682

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1190-3P7 Specifications

3a
Right-hand
0.345 Inches Minimum And 0.438 Inches Maximum
0.407 Inches Minimum And 0.438 Inches Maximum
Pan
0.357 Inches Minimum And 0.373 Inches Maximum
0.122 Inches Minimum And 0.133 Inches Maximum
Cross Recess Type 1
0.190 Inches
32
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
32.0 Microinches Bearing Surface Of Head
32.0 Microinches Threads
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd
Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Unjf
80205-nas1190 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS1190-3P7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.