

Description

Fastener Length: 3/16", Thread: 10-32, Thread Length: 1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS11903T3L
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-420-2989
Schedule B:	7318.15.6080
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N NAS1190-3T3L Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.126 Inches Maximum
Fastener Length:	0.157 Inches Minimum And 0.188 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Locking Feature:	Strip
Internal Drive Style:	Cross Recess Type Iii
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Steel Comp 4140 Or Steel Comp 4340 Or Steel Comp 8740
Locking Feature Material:	Plastic Polyamide
Screw Material Document And Classification:	Mil-s-5656 Mil Spec 1st Material Response Or Mil-s-8844 Mil Spec 2nd Material Response Or Ams 6414 Assn Std Single Material Response Or Mil-s-6049 Mil Spec 3rd Material Response
Locking Feature Material Document And Classification:	Mil-f-18240 Mil Spec Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416, Type Class 2 Fed Spec All Treatment Responses
Bearing Surface Of Head Surface Finish:	32.0 Microinches
Shank Surface Finish:	32.0 Microinches
Thread Surface Finish:	32.0 Microinches
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1190 Professional/Industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1190-3T3L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.