

P/N NAS1190E02P-4

Description

Fastener Length: 1/4", Thread: 2-56, Thread Length: 1/4

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

Alternate Part Numbers

NAS1190E02P4

SKU / Model: NAS1190E02P4

Minimum Qty (MOQ): 20

NSN: 5305-00-372-9986

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1190E02P-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.183 Inches Minimum And 0.250 Inches Maximum
Fastener Length:	0.219 Inches Minimum And 0.250 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.155 Inches Minimum And 0.167 Inches Maximum
Head Height:	0.053 Inches Minimum And 0.062 Inches Maximum
Locking Feature:	Patch Or Pellet Or Strip
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Steel Corrosion Resisting
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1190 Professional/industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1190E02P-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1190E02P-4 and selecting the