

**Description**

Fastener Length: 3/16", Thread: 2-56, Thread Length: 3/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1190E02P3B
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-233-9758
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1190E02P3B Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.121 Inches Minimum And 0.188 Inches Maximum
<b>Fastener Length:</b>	0.157 Inches Minimum And 0.188 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.155 Inches Minimum And 0.167 Inches Maximum
<b>Head Height:</b>	0.053 Inches Minimum And 0.062 Inches Maximum
<b>Locking Feature:</b>	Patch Threads
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.086 Inches
<b>Thread Quantity Per Inch:</b>	56
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas1190 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1190E02P3B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.