

**Description**

Fastener Length: 5/8", Thread: 4-40, Thread Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1190E04P10B
Minimum Qty (MOQ):	20 EA
NSN:	5305-01-240-8900
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc

NO IMAGE  
AVAILABLE

## P/N NAS1190E04P10B Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.544 Inches Minimum And 0.625 Inches Maximum
<b>Fastener Length:</b>	0.594 Inches Minimum And 0.625 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.195 Inches Minimum And 0.219 Inches Maximum
<b>Head Height:</b>	0.070 Inches Minimum And 0.080 Inches Maximum
<b>Locking Feature:</b>	Patch
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Thread Quantity Per Inch:</b>	40
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Screw Material:</b>	Iron Alloy 660
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Assn Std Single Treatment Response
<b>Bearing Surface Of Head Surface Finish:</b>	63.0 Microinches
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas1190 Professional/Industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1190E04P10B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.