

P/N NAS1190E08P7

Description

Fastener Length: 7/16", Thread: 8-32, Thread Length: 27/64", NAS1190 series bolt

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS1190E08P7
Minimum Qty (MOQ):	10
NSN:	5305-01-042-4413
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



^{*} See page 2 for technical characteristics

P/N NAS1190E08P7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.422 Inches Nominal
Fastener Length:	0.407 Inches Minimum And 0.438 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Locking Feature:	Patch Threads Or Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Surface Finish:	125.0 Microinches Top Of Head
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Threads
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1190 Professional/industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1190E08P7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.