

**Description**

Fastener Length: 1/4", Thread: 4-40, Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1191E04T4                              |
| Minimum Qty (MOQ):      | 25 EA                                     |
| NSN:                    | 5305-01-021-2530                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS1191E04T4 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.169 Inches Minimum And 0.250 Inches Maximum                 |
| <b>Fastener Length:</b>                               | 0.219 Inches Minimum And 0.250 Inches Maximum                 |
| <b>Head Style:</b>                                    | Flat Chamfer  |
| <b>Head Diameter:</b>                                 | 0.178 Inches Minimum And 0.183 Inches Maximum                 |
| <b>Head Height:</b>                                   | 0.059 Inches Minimum And 0.069 Inches Maximum                 |
| <b>Locking Feature:</b>                               | Patch Threads Or Pellet Threads Or Strip Threads              |
| <b>Internal Drive Style:</b>                          | Offset Cruciform (torque Set)                                 |
| <b>Nominal Thread Diameter:</b>                       | 0.112 Inches  |
| <b>Thread Quantity Per Inch:</b>                      | 40  |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch                                 |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head                      |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads                                      |
| <b>Material:</b>                                      | Iron Alloy 660 Fastener                                       |
| <b>Material:</b>                                      | Plastic Polyamide Locking Feature                             |
| <b>Material Document And Classification:</b>          | Ams 5737 Assn Std Single Material Response Fastener           |
| <b>Material Document And Classification:</b>          | Mil-f-18240 Mil Spec Single Material Response Locking Feature |
| <b>Surface Treatment:</b>                             | Passivate Fastener  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Fastener           |
| <b>Thread Series Designator:</b>                      | Unjc  |
| <b>Specification/standard Data:</b>                   | 80205-nas1191 Professional/industrial Association Standard    |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1191E04T4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.