

Description

2 piece assembly

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1193K16CP
Minimum Qty (MOQ):	1
NSN:	5340-01-039-0482
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1193K16CP Specifications

Cross-sectional Shape Style:	Flat
End Radius:	0.135 Inches Nominal
Mounting Hole Diameter:	0.090 Inches Nominal
Mounting Hole Quantity:	1
Aperture Diameter:	1.005 Inches Minimum And 1.025 Inches Maximum
Plate Thickness:	0.072 Inches Nominal
Center To Center Distance Between Center Aperture/mounting Hole And End Mounting Hole:	0.715 Inches Nominal
Special Features:	84 Serrations
Material:	Steel, Ams 5355
Material:	Steel Comp 630
Material Document And Classification:	Ams 5355 Assn Std Single Material Response
Surface Treatment:	Cadmium And Chromate
Surface Treatment Document And Classification:	Qq-p-416, Type 2, Class 2 Fed Spec Single Treatment Response
Surface Treatment:	Cadmium, Qq-p-416, Type 2, Class 2

How to Order

Order this locking device from our inventory online by visiting <https://military-fasteners.com/shop+supplies/locking+devices/NAS1193K16CP> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.