

Description

thread: 3/8-24, two piece assembly, positive index device, corrosion resistant steel, NAS1193 series

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1193K6C
Minimum Qty (MOQ):	5
NSN:	5340-00-519-5506
Schedule B:	7318.16.0060
ECCN:	EAR99
National Motor Freight:	095760, Locks / Lock Sets Noi Metal In Bbl / Bx



* See page 2 for technical characteristics

P/N NAS1193K6C Specifications

Inside Diameter:	0.380 Inches Minimum And 0.390 Inches Maximum
Outside Diameter:	0.560 Inches Minimum And 0.580 Inches Maximum
Overall Height:	0.092 Inches Nominal
Distance From Centerline To Top Of Internal Key:	0.128 Inches Nominal
Material Thickness:	0.043 Inches Nominal
First Key Width:	0.077 Inches Minimum And 0.087 Inches Maximum
Wire Hole Diameter:	0.062 Inches Nominal
Special Features:	Both Halves In Each Set..
Material:	Steel, Ams 5355
Material:	Steel Comp 630
Material Document And Classification:	Ams 5355 Assn Std Single Material Response
Style Designator:	Plate Type
Specification/standard Data:	80205-nas1193 Professional/Industrial Association Standard

How to Order

Order this locking device from our inventory online by visiting <https://military-fasteners.com/shop+supplies/locking+devices/NAS1193K6C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.