

**Description**

thread: 3/8-24, two piece assembly, positive index device, corrosion resistant steel, NAS1193 series

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1193K6C
Minimum Qty (MOQ):	5
NSN:	5340-00-519-5506
Schedule B:	7318.16.0060
ECCN:	EAR99
National Motor Freight:	095760, Locks / Lock Sets Noi Metal In Bbl / Bx



## P/N NAS1193K6C Specifications

<b>Inside Diameter:</b>	0.380 Inches Minimum And 0.390 Inches Maximum
<b>Outside Diameter:</b>	0.560 Inches Minimum And 0.580 Inches Maximum
<b>Overall Height:</b>	0.092 Inches Nominal
<b>Distance From Centerline To Top Of Internal Key:</b>	0.128 Inches Nominal
<b>Material Thickness:</b>	0.043 Inches Nominal
<b>First Key Width:</b>	0.077 Inches Minimum And 0.087 Inches Maximum
<b>Wire Hole Diameter:</b>	0.062 Inches Nominal
<b>Special Features:</b>	Both Halves In Each Set..
<b>Material:</b>	Steel, Ams 5355
<b>Material:</b>	Steel Comp 630
<b>Material Document And Classification:</b>	Ams 5355 Assn Std Single Material Response
<b>Style Designator:</b>	Plate Type
<b>Specification/standard Data:</b>	80205-nas1193 Professional/Industrial Association Standard

## How to Order

Order this locking device from our inventory online by visiting <https://military-fasteners.com/shop+supplies/locking+devices/NAS1193K6C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.