

Description

Nut Length: 1/2

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1195C3KH
Minimum Qty (MOQ):	50
NSN:	5310-00-181-6911
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1195C3KH Specifications

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	0.506 Inches Minimum And 0.521 Inches Maximum
Thru-hole Diameter:	0.210 Inches Minimum And 0.220 Inches Maximum
Plate Thickness:	0.057 Inches Minimum And 0.069 Inches Maximum
Plate Width:	0.313 Inches Minimum And 0.328 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.247 Inches Minimum And 0.253 Inches Maximum
Center To Center Distance Between Mounting Holes Along Width:	0.217 Inches Minimum And 0.221 Inches Maximum
Material:	Steel Comp 301 Overall Or Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall
Material Document And Classification:	Mil-s-6721 Mil Spec 1st Material Response Overall Or Mil-s-5059 Mil Spec 2nd Material Response Overall
Specification/standard Data:	80205-nas1195 Professional/industrial Association Standard

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1195C3KH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.