

**Description**

Nut Length: 3/4", nutplate spacer shim,

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1195C3WH
Minimum Qty (MOQ):	20
NSN:	5310-00-812-7903
Schedule B:	7318.16.0030
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



\* See page 2 for technical characteristics

## P/N NAS1195C3WH Specifications

<b>Mounting Hole Diameter:</b>	0.102 Inches Minimum And 0.108 Inches Maximum
<b>Nut Style:</b>	Plate Nut Spacer
<b>Nut Length:</b>	0.724 Inches Maximum
<b>Thru-hole Diameter:</b>	0.210 Inches Minimum And 0.220 Inches Maximum
<b>Plate Thickness:</b>	0.063 Inches Nominal
<b>Plate Width:</b>	0.328 Inches Maximum
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.247 Inches Minimum And 0.253 Inches Maximum
<b>Center To Center Distance Between Mounting Holes Along Length:</b>	0.498 Inches Minimum And 0.502 Inches Maximum
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Mil-s-6721 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Specification/standard Data:</b>	80205-nas1195 Professional/Industrial Association Standard

## How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1195C3WH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.