

P/N NAS1195C4XM

Description

Nut Length: 3/4

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS1195C4XM

Minimum Qty (MOQ): 15

NSN: 5310-01-015-9692

Schedule B: 7318.15.5030

ECCN: 9A991

National Motor Freight: 194160, Washer Or Gaskets, Iron Or Steel,



^{*} See page 2 for technical characteristics

P/N NAS1195C4XM Specifications

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	0.786 Inches Minimum And 0.801 Inches Maximum
Thru-hole Diameter:	0.322 Inches Minimum And 0.332 Inches Maximum
Plate Thickness:	0.026 Inches Minimum And 0.038 Inches Maximum
Plate Width:	0.485 Inches Minimum And 0.500 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.278 Inches Minimum And 0.284 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.559 Inches Minimum And 0.563 Inches Maximum
Material:	Steel Comp 301 Overall Or Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Corrosion Resisting Overall
Material Document And Classification:	Mil-s-5059 Mil Spec 1st Material Response Overall Or Mil-s-5059 Mil Spec 2nd Material Response Overall Or Mil-s-5059 Mil Spec 3rd Material Response Overall Or Mil-s-5059 Mil Spec 4th Material Response Overall Or Mil-s-6721 Mil Spec 5th Material Response Overall
Specification/standard Data:	80205-nas1195 Professional/industrial Association Standard

How to Order

Order this flat washer from our inventory online by visiting https://military-fasteners.com/washers/flat+washers/NAS1195C4XM and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.