

**Description**

Nut Length: 1/2

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1195D3KH
Minimum Qty (MOQ):	35
NSN:	5310-00-458-1961
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013540, Alum Nuts

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1195D3KH Specifications

<b>Mounting Hole Diameter:</b>	0.102 Inches Minimum And 0.108 Inches Maximum
<b>Nut Style:</b>	Plate Nut Spacer
<b>Nut Length:</b>	0.506 Inches Minimum And 0.521 Inches Maximum
<b>Thru-hole Diameter:</b>	0.210 Inches Minimum And 0.220 Inches Maximum
<b>Plate Thickness:</b>	0.057 Inches Minimum And 0.069 Inches Maximum
<b>Plate Width:</b>	0.313 Inches Minimum And 0.328 Inches Maximum
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.247 Inches Minimum And 0.253 Inches Maximum
<b>Center To Center Distance Between Mounting Holes Along Width:</b>	0.217 Inches Minimum And 0.221 Inches Maximum
<b>Special Features:</b>	Dyed Orange
<b>Material:</b>	Aluminum Alloy 5052 Overall
<b>Material Document And Classification:</b>	Qq-a-250/8,alloy 5052,temper H34 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1195 Professional/industrial Association Standard

## How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1195D3KH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.