

Description

Nut Length: 11/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1195DD08WH
Minimum Qty (MOQ):	65
NSN:	5310-00-903-3648
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013540, Alum Nuts

NO IMAGE
AVAILABLE

P/N NAS1195DD08WH Specifications

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	0.677 Inches Minimum And 0.692 Inches Maximum
Thru-hole Diameter:	0.180 Inches Minimum And 0.190 Inches Maximum
Plate Thickness:	0.057 Inches Minimum And 0.069 Inches Maximum
Plate Width:	0.282 Inches Minimum And 0.297 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.231 Inches Minimum And 0.237 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.466 Inches Minimum And 0.470 Inches Maximum
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-p-250/12 Fed Spec Single Material Response Overall
Specification/standard Data:	80205-nas1195 Professional/Industrial Association Standard

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1195DD08WH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.