

Description

Nut Length: 11/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1195DD08WM
Minimum Qty (MOQ):	5
NSN:	5310-01-321-8593
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1195DD08WM Specifications

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	0.677 Inches Minimum And 0.692 Inches Maximum
Thru-hole Diameter:	0.180 Inches Minimum And 0.190 Inches Maximum
Plate Thickness:	0.026 Inches Minimum And 0.038 Inches Maximum
Plate Width:	0.282 Inches Minimum And 0.297 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.231 Inches Minimum And 0.237 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.466 Inches Minimum And 0.470 Inches Maximum
Material:	Aluminum Alloy 2014 Overall Or Aluminum Alloy 2024 Overall Or Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-250/3 Fed Spec 1st Material Response Overall Or Qq-a-250/5 Fed Spec 2nd Material Response Overall Or Qq-a-250/13 Fed Spec 3rd Material Response Overall
Surface Treatment:	Anodize Overall And Chromate Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2 Mil Spec 1st Treatment Response Overall And Mil-c-5541,cl 3 Mil Spec 2nd Treatment Response Overall
Specification/standard Data:	80205-nas1195 Professional/industrial Association Standard

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1195DD08WM> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.