



Military-Fasteners.com

P/N NAS1195DD08XM

Description

Nut Length: 45/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1195DD08XM |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5310-00-983-9111 |
| Schedule B: | 7616.10.1000 |
| ECCN: | EAR99 |
| National Motor Freight: | 194120, Washers / Gaskets / Pckg Dvcs Noi |



* See page 2 for technical characteristics

P/N NAS1195DD08XM Specifications

| | |
|--|---|
| Mounting Hole Diameter: | 0.102 Inches Minimum And 0.108 Inches Maximum |
| Nut Style: | Plate Nut Spacer |
| Nut Length: | 0.692 Inches Minimum And 0.707 Inches Maximum |
| Thru-hole Diameter: | 0.240 Inches Minimum And 0.250 Inches Maximum |
| Plate Thickness: | 0.026 Inches Minimum And 0.038 Inches Maximum |
| Plate Width: | 0.352 Inches Minimum And 0.367 Inches Maximum |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.231 Inches Minimum And 0.237 Inches Maximum |
| Center To Center Distance Between Mounting Holes Along Length: | 0.466 Inches Minimum And 0.470 Inches Maximum |
| Material: | Aluminum Alloy 2014 Overall Or Aluminum Alloy 2024 Overall Or Aluminum Alloy 7075 Overall |
| Material Document And Classification: | Qq-a-250/3,t6 Fed Spec 1st Material Response Overall Or Qq-a-250/5,t3 Or T4 Fed Spec 2nd Material Response Overall Or Qq-a-250/13,t6 Fed Spec 3rd Material Response Overall |
| Specification/standard Data: | 80205-nas1195 Professional/industrial Association Standard |

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1195DD08XM> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.