

**Description**

Nut Length: 33/64

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                   |
|-------------------------|-------------------|
| SKU / Model:            | NAS1195DD3FH      |
| Minimum Qty (MOQ):      | 20                |
| NSN:                    | 5310-00-975-2025  |
| Schedule B:             | 7616.10.1000      |
| ECCN:                   | 9A991             |
| National Motor Freight: | 013540, Alum Nuts |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1195DD3FH Specifications

|   |  |
|---|--|
| <b>Mounting Hole Diameter:</b>                                | 0.102 Inches Minimum And 0.108 Inches Maximum              |
| <b>Nut Style:</b>   | Plate Nut Spacer   |
| <b>Nut Length:</b>  | 0.511 Inches Minimum And 0.526 Inches Maximum              |
| <b>Thru-hole Diameter:</b>                                    | 0.313 Inches Minimum And 0.328 Inches Maximum              |
| <b>Plate Thickness:</b>                                       | 0.057 Inches Minimum And 0.069 Inches Maximum              |
| <b>Nut Mounting Provision:</b>                                | Straight Holes   |
| <b>Mounting Hole Arrangement Style:</b>                       | 2 Holes  |
| <b>Distance From Aperture Center To Mounting Hole Center:</b> | 0.247 Inches Minimum And 0.253 Inches Maximum              |
| <b>Material:</b>  | Aluminum Alloy Overall                                     |
| <b>Surface Treatment:</b>                                     | Anodize Overall  |
| <b>Specification/standard Data:</b>                           | 80205-nas1195 Professional/industrial Association Standard |

## How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1195DD3FH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.