

## P/N NAS1195DD3FH

### **Description**

Nut Length: 33/64

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

# Order this part online

#### **Additional Information**

SKU / Model:	NAS1195DD3FH
Minimum Qty (MOQ):	20
NSN:	5310-00-975-2025
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	013540, Alum Nuts



<sup>\*</sup> See page 2 for technical characteristics

## **P/N NAS1195DD3FH Specifications**

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	0.511 Inches Minimum And 0.526 Inches Maximum
Thru-hole Diameter:	0.313 Inches Minimum And 0.328 Inches Maximum
Plate Thickness:	0.057 Inches Minimum And 0.069 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.247 Inches Minimum And 0.253 Inches Maximum
Material:	Aluminum Alloy Overall
Surface Treatment:	Anodize Overall
Specification/standard Data:	80205-nas1195 Professional/industrial Association Standard

### **How to Order**

Order this flat washer from our inventory online by visiting <a href="https://military-fasteners.com/washers/flat+washers/NAS1195DD3FH">https://military-fasteners.com/washers/flat+washers/NAS1195DD3FH</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.