

P/N NAS1195DD3XM

Military-Fasteners.com

Description

Nut Length: 47/64

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS1195DD3XM
Minimum Qty (MOQ):	60
NSN:	5310-00-882-0429
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1195DD3XM Specifications

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	0.739 Inches Nominal
Thru-hole Diameter:	0.260 Inches Minimum And 0.270 Inches Maximum
Plate Thickness:	0.032 Inches Nominal
Plate Width:	0.416 Inches Nominal
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.247 Inches Minimum And 0.253 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.498 Inches Minimum And 0.502 Inches Maximum
Material:	Aluminum Alloy Overall
Specification/standard Data:	80205-nas1195 Professional/industrial Association Standard

How to Order

Order this flat washer from our inventory online by visiting <u>https://military-fasteners.com/washers/flat+washers/NAS1195DD3XM</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.