

Description

Nut Length: 13/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1195DD4EH
Minimum Qty (MOQ):	5
NSN:	5310-00-556-7074
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013540, Alum Nuts

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1195DD4EH Specifications

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	0.807 Inches Minimum And 0.822 Inches Maximum
Thru-hole Diameter:	0.270 Inches Minimum And 0.280 Inches Maximum
Plate Thickness:	0.057 Inches Minimum And 0.069 Inches Maximum
Plate Width:	0.399 Inches Minimum And 0.414 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.278 Inches Minimum And 0.284 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.217 Inches Minimum And 0.221 Inches Maximum
Material:	Aluminum Alloy 2024 Overall Or Aluminum Alloy 7075 Overall Or Aluminum Alloy 2014 Overall
Material Document And Classification:	Qq-a-250/5,alloy Alclad 2024,t3 Fed Spec 1st Material Response Overall Or Qq-a-250/5,t4 Fed Spec 2nd Material Response Overall Or Qq-a-250/13,alloy Alclad 7075,t6 Fed Spec 3rd Material Response Overall Or Qq-a-250/3,alloy 2014,t6 Fed Spec 4th Material Response Overall
Specification/standard Data:	80205-nas1195 Professional/industrial Association Standard

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1195DD4EH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.