



Military-Fasteners.com

P/N NAS1195DD4XM

Description

Nut Length: 51/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1195DD4XM
Minimum Qty (MOQ):	30
NSN:	5310-00-225-6692
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1195DD4XM Specifications

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	0.801 Inches Nominal
Thru-hole Diameter:	0.322 Inches Minimum And 0.332 Inches Maximum
Plate Thickness:	0.032 Inches Nominal
Plate Width:	0.500 Inches Nominal
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.278 Inches Minimum And 0.284 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.559 Inches Minimum And 0.563 Inches Maximum
Material:	Aluminum Alloy Overall Or Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-225 Fed Spec 1st Material Response Overall Or Qq-a-362 Fed Spec 2nd Material Response Overall
Specification/standard Data:	80205-nas1195 Professional/industrial Association Standard

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1195DD4XM> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.