

Description

Nut Length: 0-63/64

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------|
| SKU / Model: | NAS1195DD5WH |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5310-00-847-3836 |
| Schedule B: | 7616.10.1000 |
| ECCN: | 9A991 |
| National Motor Freight: | 013540, Alum Nuts |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1195DD5WH Specifications

| | |
|---|---|
| Mounting Hole Diameter: | 0.134 Inches Minimum And 0.140 Inches Maximum |
| Nut Style: | Plate Nut Spacer |
| Nut Length: | 0.991 Inches Minimum And 1.006 Inches Maximum |
| Thru-hole Diameter: | 0.330 Inches Minimum And 0.340 Inches Maximum |
| Plate Thickness: | 0.057 Inches Minimum And 0.069 Inches Maximum |
| Plate Width: | 0.490 Inches Minimum And 0.505 Inches Maximum |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.356 Inches Minimum And 0.362 Inches Maximum |
| Center To Center Distance Between Mounting Holes Along Length: | 0.716 Inches Minimum And 0.720 Inches Maximum |
| Material: | Aluminum Alloy 2014 Overall Or Aluminum Alloy 2024 Overall Or Aluminum Alloy 7075 Overall |
| Material Document And Classification: | Qq-a-250/3,t6 Fed Spec 1st Material Response Overall Or Qq-a-250/5,t3 Or T4 Fed Spec 2nd Material Response Overall Or Qq-a-250/13,t6 Fed Spec 3rd Material Response Overall |
| Specification/standard Data: | 80205-nas1195 Professional/industrial Association Standard |

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1195DD5WH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.