

Description

Nut Length: 0-63/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1195DD5WH
Minimum Qty (MOQ):	10
NSN:	5310-00-847-3836
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	013540, Alum Nuts



\* See page 2 for technical characteristics

# P/N NAS1195DD5WH Specifications

Mounting Hole Diameter:	0.134 Inches Minimum And 0.140 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	0.991 Inches Minimum And 1.006 Inches Maximum
Thru-hole Diameter:	0.330 Inches Minimum And 0.340 Inches Maximum
Plate Thickness:	0.057 Inches Minimum And 0.069 Inches Maximum
Plate Width:	0.490 Inches Minimum And 0.505 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.356 Inches Minimum And 0.362 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.716 Inches Minimum And 0.720 Inches Maximum
Material:	Aluminum Alloy 2014 Overall Or Aluminum Alloy 2024 Overall Or Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-250/3,t6 Fed Spec 1st Material Response Overall Or Qq-a-250/5,t3 Or T4 Fed Spec 2nd Material Response Overall Or Qq-a-250/13,t6 Fed Spec 3rd Material Response Overall
Specification/standard Data:	80205-nas1195 Professional/industrial Association Standard

## How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1195DD5WH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.