

Description

size: 5/16 thickness: 1/64", aluminum alloy, NAS1197 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1197516L |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5310-00-184-8980 |
| Schedule B: | 7616.10.9090 |
| ECCN: | EAR99 |
| National Motor Freight: | 194120, Washers / Gaskets / Pckg Dvcs Noi |

NO IMAGE
AVAILABLE

P/N NAS1197-516L Specifications

| | |
|---|--|
| Cross-sectional Shape Style: | Rectangular |
| Hole Diameter: | 0.318 Inches Minimum And 0.338 Inches Maximum |
| Peripheral Shape Style: | Round |
| Center Hole Shape Style: | 1 Round |
| Center Hole Shape Style: | Round |
| Thickness: | 0.013 Inches Minimum And 0.019 Inches Maximum |
| Overall Diameter: | 0.557 Inches Minimum And 0.582 Inches Maximum |
| Material: | Aluminum Alloy 2024 Overall |
| Material Document And Classification: | Qq-a-250/5 Fed Spec Single Material Response Overall |
| Surface Treatment: | Oxide Film Overall Or Anodize Overall |
| Surface Treatment Document And Classification: | Mil-c-5541 Mil Spec 1st Treatment Response Overall Or Mil-a-8625 Mil Spec 2nd Treatment Response Overall |

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1197-516L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.