

Description

Fastener Length: 9/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS119849 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5320-00-959-7459 |
| Schedule B: | 7318.23.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N NAS1198-4-9 Specifications

| | |
|---|--|
| Fastener Length: | 0.563 Inches Nominal |
| Head Style: | Universal |
| Head Height: | 0.054 Inches Minimum And 0.064 Inches Maximum |
| Shank Diameter: | 0.123 Inches Minimum And 0.126 Inches Maximum |
| Shank Style: | Countersunk (undrilled) |
| Head Major Diameter: | 0.238 Inches Minimum And 0.262 Inches Maximum |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1198-4-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.