

Description

Fastener Length: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS119853
Minimum Qty (MOQ):	145 EA
NSN:	5320-00-354-6483
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1198-5-3 Specifications

Fastener Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Tapered Hollow
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Shank End Hole Diameter:	0.080 Inches Nominal
Hole Depth:	Any Acceptable
Shear Strength:	85000 Single Pounds Per Square Inch
Heat Treatment:	Solution Heat Treated Overall
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1198 Professional/industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1198-5-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.