

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS119934
Minimum Qty (MOQ):	200 EA
NSN:	5320-00-188-1622
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1199-3-4 Specifications

Fastener Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Countersunk (undrilled)
Head Major Diameter:	0.1548 Inches Minimum And 0.1900 Inches Maximum
Shear Strength:	85000 Single Pounds Per Square Inch
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Heat Treatment:	Solution Heat Treated Overall
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1199 Professional/Industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1199-3-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.