



Military-Fasteners.com

P/N NAS1199-3-7

## Description

Fastener Length: 1/2

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS119937
Minimum Qty (MOQ):	100
NSN:	5320-00-007-9953
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N NAS1199-3-7 Specifications

<b>Fastener Length:</b>	0.428 Inches Minimum And 0.448 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.093 Inches Minimum And 0.097 Inches Maximum
<b>Shank Style:</b>	Countersunk (undrilled)
<b>Head Major Diameter:</b>	0.190 Inches Maximum
<b>Shear Strength:</b>	85000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Heat Treatment:</b>	Solution Heat Treated Overall
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1199 Professional/industrial Association Standard

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1199-3-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.