

Description

Fastener Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS119939 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-01-030-1880 |
| Schedule B: | 7318.23.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1199-3-9 Specifications

| | |
|---|--|
| Fastener Length: | 0.553 Inches Minimum And 0.573 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.094 Inches Nominal |
| Shank Style: | Countersunk (undrilled) |
| Head Major Diameter: | 0.1548 Inches Minimum And 0.1900 Inches Maximum |
| Shear Strength: | 85000 Single Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Heat Treatment: | Solution Heat Treated Overall |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1199 Professional/industrial Association Standard |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1199-3-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.