

**Description**

Fastener Length: 5/16, roughly 485 pieces per pound

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS119955                                   |
| Minimum Qty (MOQ):      | 50  |
| NSN:                    | 5320-00-173-8797                            |
| Schedule B:             | 7318.23.0000                                |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE  
AVAILABLE

## P/N NAS1199-5-5 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.302 Inches Minimum And 0.322 Inches Maximum                                  |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>                                | 0.155 Inches Minimum And 0.160 Inches Maximum                                  |
| <b>Shank Style:</b>                                   | Countersunk (undrilled)  |
| <b>Head Major Diameter:</b>                           | 0.2566 Inches Minimum And 0.2976 Inches Maximum                                |
| <b>Shear Strength:</b>                                | 85000 Single Pounds Per Square Inch  |
| <b>Countersink Angle:</b>                             | 98.5 Degrees Minimum And 101.5 Degrees Maximum                                 |
| <b>Heat Treatment:</b>                                | Solution Heat Treated Overall  |
| <b>Material:</b>                                      | Iron Alloy 660 Overall   |
| <b>Material Document And Classification:</b>          | Ams 5737 Assn Std Single Material Response Overall                             |
| <b>Surface Treatment:</b>                             | Passivate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall                             |
| <b>Specification/standard Data:</b>                   | 80205-nas1199 Professional/industrial Association Standard                     |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1199-5-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.