

Description

Fastener Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | NAS1200M510 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5320-01-331-7649 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |



* See page 2 for technical characteristics

P/N NAS1200M5-10 Specifications

| | |
|--|--|
| Fastener Length: | 0.615 Inches Minimum And 0.635 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.155 Inches Minimum And 0.160 Inches Maximum |
| Shank Style: | Countersunk (undrilled) |
| Head Major Diameter: | 0.225 Inches Minimum And 0.247 Inches Maximum |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Nickel Alloy 400 Overall |
| Material Document And Classification: | Qq-n-281,cl A Fed Spec Single Material Response Overall |
| Specification/standard Data: | 80205-nas1200 Professional/industrial Association Standard |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1200M5-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.