

Description

Fastener Length: 1-1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1200M520
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-232-4292
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE
AVAILABLE

P/N NAS1200M5-20 Specifications

Fastener Length:	1.240 Inches Minimum And 1.260 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Countersunk (undrilled)
Head Major Diameter:	0.2469 Inches Maximum
Shear Strength:	49000 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Heat Treatment:	Annealed Overall
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Overall
Specification/standard Data:	80205-nas1200 Professional/industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1200M5-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.