



Military-Fasteners.com

P/N NAS1200M5-4P

Description

Fastener Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1200M54P
Minimum Qty (MOQ):	100
NSN:	5320-01-068-5541
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N NAS1200M5-4P Specifications

Fastener Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.2469 Inches Maximum
Shear Strength:	49000 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Heat Treatment:	Annealed Overall
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281,cl A Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1200 Professional/industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1200M5-4P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.