

**Description**

Fastener Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |  |
|-------------------------|--|
| SKU / Model:            | NAS1200M56P                                      |
| Minimum Qty (MOQ):      | 130 EA   |
| NSN:                    | 5320-01-150-9511                                 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |

NO IMAGE  
AVAILABLE

## P/N NAS1200M5-6P Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.365 Inches Minimum And 0.385 Inches Maximum                                  |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>                                | 0.155 Inches Minimum And 0.160 Inches Maximum                                  |
| <b>Shank Style:</b>                                   | Straight W/radius Chamfered Tip  |
| <b>Head Major Diameter:</b>                           | 0.2469 Inches Maximum  |
| <b>Shear Strength:</b>                                | 49000 Single Pounds Per Square Inch  |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum                                 |
| <b>Heat Treatment:</b>                                | Annealed Overall   |
| <b>Material:</b>                                      | Nickel Alloy 400 Overall   |
| <b>Material Document And Classification:</b>          | Qq-n-281,class A Fed Spec Single Material Response Overall                     |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall             |
| <b>Specification/standard Data:</b>                   | 80205-nas1200 Professional/industrial Association Standard                     |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1200M5-6P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.