

Description

diameter: 5/32" length: 7/16", flush shear head monel, roughly 400 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1200M57
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-076-7238
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



P/N NAS1200M5-7 Specifications

Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.2251 Inches Minimum And 0.2469 Inches Maximum
Shear Strength:	49000 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Heat Treatment:	Annealed Overall
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281,class A Fed Spec Single Material Response Overall
Specification/standard Data:	80205-nas1200 Professional/industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1200M5-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.